

VME Flex Drive Assemblies

Flex Drive Assemblies, with or without the quick disconnect drive fitting, come with a fully greased core. They are ready to connect directly to the motor. In the Assemblies with the drive fittings, Teflon[®] tape is applied to the threads of the casing before attaching the drive fitting. This ensures the fitting is secure.

	1-1/16" DIAMETER (Casing with Core Installed)		7/8" DIAMETER (Casing with Core Installed)	
DRIVE LENGTH FT	PART #	NET WT LBS	PART #	NET WT LBS
1	930001	2.0	930201	1.2
3	930003	3.8	930203	2.4
5	930005	5.7	930205	3.8
7	930007	7.7	930207	5.2
10	930010	10.4	930210	7.2
14	930014	14.6	930214	10.1
21	930021	21.2	930221	14.7

VME Flex Drive Assemblies with Quick Disconnect

Quick Disconnect allows quick and easy removal of flex drive from motor without tools. Just turn the nut clockwise while facing the face plate (flex drive end).

	1-1/16" DIAMETER (Casing with Core Installed)		7/8" DIAMETER (Casing with Core Installed)	
DRIVE LENGTH FT	PART #	NET WT LBS	PART #	NET WT LBS
1	930601	2.3	930801	1.5
3	930603	4.1	930803	2.7
5	930605	6.0	930805	4.1
7	930607	8.0	930807	5.5
10	930610	10.7	930810	7.5
14	930614	14.9	930814	10.4
21	930621	21.5	930821	15.0

CHICAGO VIBRATOR PRODUCTS
WESTMONT, IL
1-800-842-7284 (USA & CANADA)
630-920-9411